


TFF CWDM 3 Ports Device

Features

- Automatic Optical alignment
- Optical path epoxy free
- Low insert loss & high isolation
- Telcordia-GR-1221-Core qualified
- RoHS compliant

Applications

- PON system
- FTTx network
- CWDM system
- Add/drop channel



Specifications

Parameter	Unit	Specification	
Channel Center Wavelength	nm	1270,1290...1610 or 1271, 1291...1611	
Channel Spacing	nm	20	
Bandwidth@-0.5dB	nm	$\geq 13 (\lambda_c \pm 6.5\text{nm})$	
Port of Transmission (Port1=>Port2)	Transmission Insertion Loss	dB	≤ 0.6 (Typical 0.4)
	Adjacent Channel Isolation	dB	> 30
	Non-Adjacent Channel Isolation	dB	> 45
	Pass Band Ripple	dB	≤ 0.3
	PDL	dB	≤ 0.15
Port of Reflection (Port1=>Port3)	Reflection Insertion Loss	dB	≤ 0.5 (Typical 0.3)
	PDL	dB	≤ 0.15
	Isolation of Reflection @ Pass Band	dB	≥ 13
Insertion Loss Temperature Stability	dB / $^{\circ}\text{C}$	≤ 0.005	
Wavelength Temperature Stability	nm / $^{\circ}\text{C}$	≤ 0.003	
Return Loss	dB	≥ 45	
Polarization Mode Dispersion	Ps	≤ 0.10	
Directivity	dB	≥ 45	
Power Handling	mW	300	
Operating Temperature	$^{\circ}\text{C}$	-40~+85	
Storage Temperature	$^{\circ}\text{C}$	-40~+85	
Fiber Type	--	Corning SMF-28 Ultra, G657A1/A2 or customer specified	

Information and specifications are subject to change without notice.
Please visit www.china-tscom.com for more information

8 Jinxiu Middle Road, Pingshan, Shenzhen, Guangdong, 518118, P. R. China
+86 755 32983688 | info@china-tscom.com | www.china-tscom.com



Pigtail type	--	Ø250µm Bare Fiber or Ø0.9mm loose tube
Fiber length	m	1.0 ,or customer specified
Package Dimension	mm	Steel Tube: Ø5.5x34 for 250µm bare fiber, Ø5.5x38 for Ø0.9mm loose tube; Glass Tube: Ø4.0x26 for Ø250µm bare fiber, Ø3.2x26 for Ø250µm bare fiber;

Note:

- Insertion loss excluding connector loss. With connectors add 0.3dB;
- Connectors can be customized on request.